

Detailed Specs

Specification	T-10HD	T-12HD	T-14HD
Capacity (pounds)	10,000	12,000	14,000
GVWR (pounds)	13,700	15,700	17,800
GAWR (pounds)	14,000	14,000	16,400
Avg. Weight (pounds)	4,300	4,300	4,400
Load Width (in)	82"	82"	82"
Deck Height (in) unloaded	25"	25"	25"
Std. Hitch Size (in)	2-5/16"	2-5/16"	2-5/16"
Tongue/Gooseneck Length (ft)	4'-7"	4'-7"	4'-7"
Safety Chain	3/8 Gr. 43	3/8 Gr. 43	3/8 Gr. 70
Parking Jack	12K	12K	12K
Bolted-on Parking Jack	Y	Y	Y
Main Frame	4x6 Tube	4x6 Tube	4x6 Tube
Deck Type	Dump Body	Dump Body	Dump Body
Deck Safety Lip	N/A	N/A	N/A
Deck Material	Steel	Steel	Steel
Added Stationary Deck	N/A	N/A	N/A
Ramps w/storage	S	S	S
Load Angle (degrees)	N/A	N/A	N/A
Dump Angle	45	45	45
Beavertail	N/A	N/A	N/A
Ramp Hold-Up	N/A	N/A	N/A
Ramp Spring Assist (off deck)	N/A	N/A	N/A
Ramp Spring Assist (off ground)	N/A	N/A	N/A
Stake Pockets	10	10	10
D-rings	4	4	4
Axle Capacity	7K	7K	8K
No. of Axles	2	2	2
Axle Spread (in)	34"	34"	34"
Hubs	EZ-Lube	EZ-Lube	EZ-Lube
Brake Size	12" x 2"	12" x 2"	12.25" x 3.38"
Electric Brakes	Std.	Std.	Std.
Air Brakes	N/A	N/A	N/A
Wheels (size)	16"	16"	17.5"
Wheel Bolt Pattern	8-bolt	8-bolt	8-bolt
Tires	235/85Rx16	235/85Rx16	215/75Rx17.5
Tire Load Rating	E	E	H
Lights	LED	LED	LED
Full Warranty	1 Year	1 Year	1 Year
Frame Warranty	1 Year	1 Year	1 Year