

Detailed Specs

| Specification | T-10HD | T-12HD | T-14HD |
|---------------------------------|------------|------------|----------------|
| Capacity (pounds) | 10,000 | 12,000 | 14,000 |
| GVWR (pounds) | 13,700 | 15,700 | 17,800 |
| GAWR (pounds) | 14,000 | 14,000 | 16,400 |
| Avg. Weight (pounds) | 4,300 | 4,300 | 4,400 |
| Load Width (in) | 82" | 82" | 82" |
| Deck Height (in) unloaded | 25" | 25" | 25" |
| Std. Hitch Size (in) | 2-5/16" | 2-5/16" | 2-5/16" |
| Tongue/Gooseneck Length (ft) | 4'-7" | 4'-7" | 4'-7" |
| Safety Chain | 3/8 Gr. 43 | 3/8 Gr. 43 | 3/8 Gr. 70 |
| Parking Jack | 12K | 12K | 12K |
| Bolted-on Parking Jack | Y | Y | Y |
| Main Frame | 4x6 Tube | 4x6 Tube | 4x6 Tube |
| Deck Type | Dump Body | Dump Body | Dump Body |
| Deck Safety Lip | N/A | N/A | N/A |
| Deck Material | Steel | Steel | Steel |
| Added Stationary Deck | N/A | N/A | N/A |
| Ramps w/storage | S | S | S |
| Load Angle (degrees) | N/A | N/A | N/A |
| Dump Angle | 45 | 45 | 45 |
| Beavertail | N/A | N/A | N/A |
| Ramp Hold-Up | N/A | N/A | N/A |
| Ramp Spring Assist (off deck) | N/A | N/A | N/A |
| Ramp Spring Assist (off ground) | N/A | N/A | N/A |
| Stake Pockets | 10 | 10 | 10 |
| D-rings | 4 | 4 | 4 |
| Axle Capacity | 7K | 7K | 8K |
| No. of Axles | 2 | 2 | 2 |
| Axle Spread (in) | 34" | 34" | 34" |
| Hubs | EZ-Lube | EZ-Lube | EZ-Lube |
| Brake Size | 12" x 2" | 12" x 2" | 12.25" x 3.38" |
| Electric Brakes | Std. | Std. | Std. |
| Air Brakes | N/A | N/A | N/A |
| Wheels (size) | 16" | 16" | 17.5" |
| Wheel Bolt Pattern | 8-bolt | 8-bolt | 8-bolt |
| Tires | 235/85Rx16 | 235/85Rx16 | 215/75Rx17.5 |
| Tire Load Rating | E | E | H |
| Lights | LED | LED | LED |
| Full Warranty | 1 Year | 1 Year | 1 Year |
| Frame Warranty | 1 Year | 1 Year | 1 Year |