

# Construction

# Steel Side Dump Trailers



## Specifications

Model	TK40SSD-202P	TK40SSD-302	TK60SSD-362	TK60SSD-402	TK60SSD-433	TK60SSD-484
Design payload	40,000 lbs.	40,000 lbs.	60,000 lbs.	60,000 lbs.	60,000 lbs.	60,000 lbs.
Axles	2	2	2	2	3	4
Overall length	20' 0"	29' 6"	35' 6"	39' 6"	42' 11"	47' 6"
Tub length	18' 0"	28' 0"	34' 0"	34' 0"	36' 0"	36' 0"
Overall height	9' 4"	9' 4"	9' 4"	9' 4"	9' 4"	9' 4"
Capacity (water level)	11.5 cu. yds.	17.3 cu. yds.	21 cu. yds.	21 cu. yds.	23 cu. yds.	23 cu. yds.
Capacity (full)	15.5 cu. yds.	24 cu. yds.	29 cu. yds.	29 cu. yds.	31 cu. yds.	31 cu. yds.
KP to center last axle	axle to axle = 15' 9"	25' 6"	31' 6"	35' 6"	38' 11"	43' 6"
Empty weight +/- 3%	10,260 lbs.	12,745 lbs.	14,010 lbs.	14,310 lbs.	16,350 lbs.	19,240 lbs.

All dimensions are approximate and are subject to change without notice.

## Standard Features

- Hardox 450 Abrasion Resistant Tub
- 5" Dia. Hydraulic Cylinders
- 3-Leaf Spring Suspension
- Automatic Slack Adjusters w/ 16 1/2" x 7" Air Brakes
- 8.25 x 22.5 Steel Wheels
- 11R22.5 x 14 Radial Tires
- Pin Style Landing Gear
- Impact-absorbent Plastic Fenders - Front & Rear
- Lightweight Push Block
- Incandescent Lights

**Distributed by:**



# TRAIL KING Industries

STEEL SIDE DUMP

2130 3rd Avenue NW ■ West Fargo, ND 58078 ■ 800-762-5557 U.S. & Canada ■ 701-282-3013 ■ Fax: 701-282-3039 ■ [www.trailking.com](http://www.trailking.com)

All rights reserved Trail King Industries, Inc. FORM SSD 2/2012-2.5